



cod.	Ø	pz/pcs	C	ØG	sp	R	bullone	cusc	binario	portata
400.40	40	12	16	Ø33	12	4,5	M8x30	1	-	60 kg.
400.50	50	12	16	Ø40	13	4,5	M8x30	1	-	80 kg.
400.60/12	60/12	12	24	Ø48	17	5,3	M10x45	1	-	100 kg.
400.60/16	60/16	12	33	Ø48	20	8,3	M10x45	1	art. 902 Ø16	100 kg.
400.70/16	70/16	6	33	Ø54	20	8,3	M14x70	1	art. 902 Ø16	190 kg.
400.80/16	80/16	6	33	Ø64	20	8,3	M14x70	1	art. 902 Ø16	200 kg.
400.80/20	80/20	6	33	Ø59	24	10,3	M14x70	1	art. 902 Ø20	200 kg.
400.90/16	90/16	6	33	Ø74	21	8,3	M14x70	1	art. 902 Ø16	210 kg.
400.90/20	90/20	6	33	Ø69	24	10,3	M14x70	1	art. 902 Ø20	210 kg.
400.100/16	100/16	6	33	Ø84	21	8,3	M14x70	1	art. 902 Ø16	230 kg.
400.100/20	100/20	6	33	Ø79	24	10,3	M14x70	1	art. 902 Ø20	230 kg.
400.120	120	4	33	Ø99	24	10,3	M14x70	1	art. 902 Ø20	250 kg.
400.140	140	4	43	Ø117	24	10,3	M16x70	1	art. 902 Ø20	280 kg.
400.160	160	2	43	Ø137	25	10,3	M16x70	1	art. 902 Ø20	300 kg.
400.200	200	2	43	Ø177	25	10,3	M16x70	1	art. 902 Ø20	340 kg.