



cod.	Ø	pz/pcs	A	B	C	D	ØG	sp	R	cusc	binario	portata
415.60/12	60/12	12	62	21	24	51	Ø48	17	5,3	1	-	100 kg.
415.60/16	60/16	12	62	21	33	51	Ø48	20	8,3	1	-	100 kg.
415.70/16	70/16	6	80	19	33	54	Ø54	20	8,3	1	art. 902 Ø16	190 kg.
415.80/16	80/16	6	80	19	33	59	Ø64	20	8,3	1	art. 902 Ø16	200 kg.
415.80/20	80/20	6	80	19	33	59	Ø59	24	10,3	1	art. 902 Ø20	200 kg.
415.90/16	90/16	6	100	22	31	67	Ø74	21	8,3	1	art. 902 Ø16	210 kg.
415.90/20	90/20	6	100	22	33	67	Ø69	24	10,3	1	art. 902 Ø20	210 kg.
415.100/16	100/16	6	100	28,5	31	78,5	Ø84	21	8,3	1	art. 902 Ø16	230 kg.
415.100/20	100/20	6	100	28,5	33	78,5	Ø79	24	10,3	1	art. 902 Ø20	230 kg.
415.120	120	6	120	38	33	98	Ø99	24	10,3	1	art. 902 Ø20	250 kg.
415.140	140	4	140	48,5	33	118,5	Ø117	24	10,3	1	art. 902 Ø20	280 kg.